





# SHUTTER & TRACK INSTALLATION INSTRUCTIONS



## 1 Determine your chosen style of installation:



Shutters can be fitted to slide open and closed using the track system.




Shutters can be fitted side by side with or without the track system.




\*Hinges not included.


## 2 The optimum height of the opening for installation is 2120mm $\pm$ 5mm.



Distance is suitable to fit the top channel to the beam.



Add spacer under beam to achieve the optimum distance.



Add spacer to side of beam to achieve the optimum distance.

### Product Care:

**Shutters:** Our range is made of lightweight powder coated aluminium that should, if used correctly and properly cared for, remain rust free for the life of your shutters.

Particular care must be taken when exposed to a salty environment.

To clean, use a small amount of mild soapy water and rinse clean. Do not use abrasive products or chemicals. We recommend using a soft microfibre cloth to avoid damage to the finish of the shutters.

**Tracks:** Ensure tracks are kept clean and are free of dust and dirt to prevent damage and resulting in operational defects.

If your shutter is scraping on its track, do not operate. Operation of shutters in this instance will cause damage and lead to roller failure.

## 3 Upper channel installation:



a. Fix spacer timber to top beam (if required).



b. Pre-drill channel to allow wood screws to be inserted.



c. Attach upper channel to beam/spacer with wood screws.

## 4 Lower track installation:




a. Using a level, locate the lower track directly below the upper channel.



b. Centre of channel should be directly above the corresponding raised section on the lower track.



c. Secure lower track to the ground using appropriate screws.



d. Fit shutter panels, inserting top into upper channel first.



e. Adjust rollers until shutters move freely. Install track stoppers if required.

## 5 Alternate installation options:

**Fixed installation:** Install track stoppers to lower track, or build a custom enclosure to hold the shutters.

**Hinged installation:** Install hinges according to manufacturer instructions.